

技术参数(Technical Parameter):

4 (Item)					
5 6 Ball mill model	B 1200X4500	B 1500X5700	B 1830X7000		
5 6 Classifier model	HFZ050	HFZ100	HFZ200		
7 8 9: kW; General power of the whole	C 75	C 145	C 225		
< : Kg/h; Processing capacity: Kg/h;	800- 1000	1200- 1800	3500- 4000		
: kg/h; Production capacity: Kg/h;	480- 600	720- 1080	2100- 2400		
: um; Particle size	5D50	5- 50	4 000		
= Classifying granularity	D97	D97	21004 TD 0.36 Tc (2)	Tj0.48 Tc (1)	5j/F4 7.44 Tf9.12 0 TD 0.4 T1.00- 1
> ? @: m ² ; Fliter area	E 50	E 70	B5000 0120000X0500 10.08	Tc (5) 0.48 Tc (1) Tj.6 Tc (0)	Tj0.48 Tc (80) Tj310.08 - Tc
A : mg/m ³ ; Thickness of dust	C 40	C 40	2200 01080- 1D- 1800- 6		
Operation					

297 00

3 1 # \$ % & ' # 325 () * (All of the parameters above are according to 325 mesh quartz)
2 + , - . / # \$ % & O 1 % Z (As different material from different places, the parameter is just for your reference)

鉴定成果(Certification)

